MAXSEAL





Our high speed vinyl door opens up to 48" per second, increasing productivity while reducing energy loss.



MAXSEAL

DOOR FEATURES MS150 - MS180

- · High speed roll up door ideal for applications in:
 - Warehouses
 - Manufacturing Facilities
 - Distribution Centers
- Corrosion resistant aluminum guides for interior and exterior mounting
- · Flexible bottom seal adaptable to uneven flooring
- Simple, efficient springless engineering with only 5 moving parts providing reliability, and longevity
- Breakaway resettable bottom bar system
- · High tension curtain withstands high wind loads



TECHNICAL SPECIFICATIONS		
Opening Speed	48" per second	
Closing Speed	24" per second	
Max Size	26' x 26'	
Drive	Direct Drive VFD	
Curtain	Vinyl	
Guide Width	5 inches	
Control Panel	NEMA-4	
Vision	Full Width x 39"h (standard)	
Available Curtain Colors	Red, Yellow, Green, Blue, Black, White, Orange, Gray	
Safety Devices	Photo Eye, Electric Safety Reversing Edge, Drive Brake	
OPTIONS		
Mechanical	Hoods	

OPTIONS	
Mechanical	Hoods Reflective Stripes
Electrical	Motor Cable Sets
Safety Devices	Light Curtain Wireless Safety Reversing Edge Presence Sensor
Activation Devices	Motion Sensors Pull Cord Push Button Remotes Floor Loops

