## MAXSPEDTM





## PERFECT FOR:

High Cycle
Frequent Impacts
Parking Garages
Heavy Manufacturing
Industrial
Corrosive Environments





MAXSPEED

## DOOR FEATURES MS350, MS1000

- High speed roll up door ideal for applications in:
  - Warehouses
  - Manufacturing Facilities
  - Distribution Centers
  - Corrosive Environments
- Powder-coated steel components
- Flexible bottom seal adaptable to uneven flooring
- Simple, efficient springless engineering with only 5 moving parts providing speed, reliability, and longevity
- Flexible curtain releases from guides upon accidental impact with breakaway system
- · High tension curtain to withstand high wind loads
- RHINOMAX™ rubber curtain with lifetime warranty



TECHNICAL SPECIFICATIONS	
Opening Speed	MS350 48" per second, MS1000 21" per second
Closing Speed	24" per second
Max Size	18' x 30'
Drive	Direct Drive VFD
Curtain	<b>RHINOMAX™</b> Rubber
Guide Width	5 inches
Control Panel	NEMA-4 UL-rated
Available Curtain Colors	Black (standard) Blue, Gray (optional)
Safety Devices	Photo Eye, Electric Safety Reversing Edge, Drive Brake

OPTIONS	
Mechanical	Hoods Reflective Stripes Vision
Electrical	Motor Cable Sets
Safety Devices	Light Curtain Wireless Safety Reversing Edge Presence Sensor
Activation Devices	Motion Sensors Pull Cord Push Button Remotes Floor Loops

